

Revive Series

VINYL SINGLE HUNG

DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Single Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft2)
Revive Vinyl	Single-Hung	Standard	2460-3	R-PG35-H	0.19
Revive Vinyl	Single-Hung	Standard	3678-3	R-PG30-H	0.13
Revive Vinyl	Single-Hung	Standard	3618-3/3660-3	R-PG30-H	0.11
Revive Vinyl	Single-Hung	Standard	3024-3/3048-3	R-PG35-H	0.12
Revive Vinyl	Single-Hung	Standard	9024-3048-3	R-PG30-H	0.14
Revive Vinyl	Single-Hung	Standard	3660-2	LC-PG40-H	0.08
Revive Vinyl	Single-Hung	Standard	2424-2/2448-2	LC-PG35-H	0.16
Revive Vinyl	Single-Hung	Standard	4278-2	R-PG30-H	0.17
Revive Vinyl	Single-Hung	Standard	4218-2/4254-2	R-PG30-H	0.09
Revive Vinyl	Single-Hung	Standard	4884-1	R-PG30-H	0.10
Revive Vinyl	Single-Hung	Standard	4578-1	LC-PG35-H	0.11
Revive Vinyl	Single-Hung	DP Upgrade	4278-2	R-PG40-H	0.09

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
Operating			
1-0	2-0	4-0	7-0