

Pinnacle Series


CLAD AWNING

ELEVATIONS : OPERATING / STATIONARY


SCALE: 1/8" = 1'-0"

Rough Opp. Frame Glass	2-0 3/4	2-4 3/4	2-6 3/4	2-8 3/4	3-0 3/4	3-6 3/4	4-0 3/4	4-6 3/4	5-0 3/4
	2-0	2-4	2-6	2-8	3-0	3-6	4-0	4-6	5-0
	20	24	26	28	32	38	44	50	56
1-6 1/2 1-6 14	2014	2414	2614	2814	3214	3814	4414	5014	5614
1-8 1/2 1-8 16	2016	2416	2616	2816	3216	3816	4416	5016	5616
2-0 1/2 2-0 20	2020	2420	2620	2820	3220	3820	4420	5020	5620
2-4 1/2 2-4 24	2024	2424	2624	2824	3224	3824	4424	5024	5624
2-6 1/2 2-6 26	2026	2426	2626	2826	3226	3826	4426	5026	5626
3-0 1/2 3-0 32	2032	2432	2632	2832	3232	3832	4432	5032	5632
3-6 1/2 3-6 38	2038	2438	2638	2838	3238	3838	4438	5038	5638
4-0 1/2 4-0 44	2044	2444	2644	2844	3244	3844	4444	5044	5644
4-6 1/2 4-6 50	2050	2450	2650	2850	3250	3850	4450	5050	5650
5-0 1/2 5-0 56	2056	2456	2656	2856	3256	3856	4456	5056	5656

OPERATION



OTHER GRILLE PATTERN



CLAD UNIT SIZE INFORMATION

FOR CLAD WM 180 BRICKMOULD

ADD 2 13/16" TO FRAME WIDTH

ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WM 180 SOLID BACK BRICKMOULD

ADD 2 13/16" TO FRAME WIDTH

ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD 3 1/2 FLAT

ADD 5 7/8" TO FRAME WIDTH

ADD 3 5/16" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG

ADD 6 1/2" TO FRAME WIDTH

ADD 3 5/8" TO FRAME HEIGHT*

* ADD ADDITIONAL 7/8" FOR 1 1/4" CLAD SUBSILL
ADD ADDITIONAL 1 7/8" FOR 2 1/4" CLAD SUBSILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
PRIMED MASONRY OPENINGS ARE FOR STANDARD 180 BRICKMOULD