



# Windsor Windows and Doors

## Pinnacle Select Clad Performance Ratings

Series	Window Type	Operator Type	Performance Option	Tested Callout	Tested Frm Width (in)	Tested Frm Height (in)	PG Rating	+DP (psf)	-DP (psf)	+STP (psf)	-STP (psf)	Water (psf)	Air (cfm/ft <sup>2</sup> )	V <sub>asd</sub> (MPH)	V <sub>ult</sub> (MPH)
Pinnacle Select Clad	Awning	Push-Out	Standard	4836-1	48	36	CW-PG70-AP	70	70	105	105	10.50	0.07	165	213
	Awning	Crank-Out	Standard	6060-1	60	60	LC-PG50-AP	50	50	75	75	7.50	0.08	140	180
	Awning	Push-Out	Standard	6060-1	60	60	LC-PG40-AP	40	40	60	60	6.00	0.09	125	161
	Casement	Picture	Standard	4878	48	78	CW-PG70-FW	70	70	105	105	10.50	0.11	165	213
	Casement	Crank-Out	Standard	3096-1	30	96	R-PG65-C	65	65	98	98	9.75	0.01	159	206
	Casement	Crank-Out	Standard	4266-1	42	66	LC-PG60-C	60	60	90	90	9.00	0.05	153	198
	Casement	Push-Out	Standard	3672-1	36	72	CW-PG50-C	50	50	75	75	7.50	0.07	140	180
	Casement	Picture	Standard	7278	72	78	CW-PG50-FW	50	50	75	75	7.50	0.07	140	180
	Casement	Crank-Out	Standard	3678-1	36	78	LC-PG50-C	50	50	75	75	7.50	0.07	140	180
	Casement	Crank-Out	Standard	3684	36	84	CW-PG40-C	40	40	60	60	6.00	0.08	125	161
	Casement	Crank-Out	Standard	4272	42	72	CW-PG40-C	40	40	60	60	6.00	0.07	125	161
	Casement	Picture	Standard	7296	72	96	CW-PG40-FW	40	40	60	60	6.00	0.02	125	161
	Casement	Push-Out	Standard	3678-1	36	78	R-PG40-C	40	40	60	60	6.00	0.07	125	161
	French Casement	Push-Out	Standard	6072	60	72	CW-PG30-C	30	30	45	45	4.60	0.26	108	140

DP = Design Pressure  
STP = Structural Test Pressure

V<sub>asd</sub> = Nominal Design Wind Speed  
V<sub>ult</sub> = Ultimate Design Wind Speed