

# New Next Dimension Series

## SINGLE HUNG

## SPECIFICATIONS

### PART 1 - GENERAL

#### 1.01 SECTION INCLUDES

- A. Factory assembled vinyl single hung windows [including fixed units], glass and glazing, operable hardware, weatherstripping, and insect screen.
- B. Anchorages, attachments, and accessories.

#### 1.02 RELATED SECTIONS

- A. Section 01340 - Shop Drawings, Product Data, and Samples.
- B. Section 01610 - Delivery, Storage, and Handling.
- C. Section 01710 - Final Cleaning.
- D. Section 07200 - Batt and Blanket Insulation.
- E. Section 07920 - Sealants and Caulking.
- F. Section 08800 - Glass and Glazing.

#### 1.03 REFERENCES

- A. AMERICAN ARCHITECTURAL MANUFACTURERS ASSOCIATION (AAMA)
  - 1. AAMA/WDMA/CSA 101/I.S.2/A440-05 Standard/Specification for windows, doors, and unit skylights.
- B. AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM):
  - 1. ASTM E-283 - Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors.
  - 2. ASTM E-547 - Water Penetration of Exterior Windows, Curtain Walls, and Doors by Cyclic Static Air Pressure Difference.
  - 3. ASTM E-330 - Structural Performance of Exterior Windows, Curtain Walls, and Doors under Uniform Static Air Pressure Difference.
  - 4. ASTM E 1300- Standard Practice for Determining Load Resistance of Glass in Buildings
- C. AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI).

#### 1.04 PERFORMANCE CRITERIA

- A. Single Hung units shall meet requirements in accordance with AAMA/WDMA/CSA 101/I.S.2/A440-05.
- B. Air leakage shall not exceed 0.30 cfm per sq.ft. when tested in accordance with ASTM E-283 at 1.57 psf.
- C. No water penetration shall be allowed when tested in accordance with ASTM E-547.
- D. Window units shall withstand positive and negative wind loads without damage. The units shall be tested in accordance with ASTM E-330.

#### 1.05 SUBMITTALS

- A. Shop drawings shall be submitted in accordance with Section 01340.
- B. Product data in the form of general catalogs, test lab reports, product performance, and warranty information shall be submitted in accordance with Section 01340.
- C. Samples showing glazing, construction and finish shall be submitted in accordance with Section 01340.

#### 1.06 DELIVERY, STORAGE, AND HANDLING

- A. In compliance with Section 01610, window units shall be delivered undamaged, with protective packaging. Complete installation and finishing instructions shall be included.
- B. Store units in a clean, dry place, off the ground in a 90 degree upright position. Do not store units under direct sunlight or in temperatures exceeding 140 degrees F.

# New Next Dimension Series

## SINGLE HUNG

## SPECIFICATIONS

### PART 2 - PRODUCTS

#### 2.01 MANUFACTURER

- A. New Next Dimension Series Vinyl Single Hung Windows as manufactured by Windsor Windows & Doors.

#### 2.02 MATERIALS

- A. Frame: All frames are manufactured using high performance *uPVC* extrusion material. Each frame is 3 5/16" wide and is fusion welded at the corners, increasing strength and maximizing weather-proof performance. All frames include an aluminum reinforced fixed interlock meeting rail that is end milled to the contour of the jamb. An extruded rigid pre-punched nail fin surrounds the perimeter of the frame and is fusion welded during the manufacturing process. The nail fin is set back 1 1/4" from the outside face of the unit leaving an interior jamb width of 2 1/16". Factory or field applied veneer-wrapped jamb extensions are available up to 7 1/4". An accessory groove surrounds the perimeter of the interior and exterior to facilitate the attachment of mull strips or drywall and jamb extension receivers. Each frame contains sloped sill for drainage that works in conjunction with the sash to remove any moisture that may accumulate from heavy rain or condensation.
- B. Sash: All sash are manufactured using high performance *uPVC* extrusion material. Lower sash corner is fusion welded, increasing strength and maximizing weather-proof performance. Triple weatherstrip seals are placed on the around the sash perimeter to further enhance performance. Lower sash contains an interior drainage system that removes any moisture that may accumulate from heavy rain or condensation. Top rail of operating sash includes an extruded interlock that engages tightly with the fixed interlock and an extruded lift rail as affixed to the bottom rail for greater ease of use. Up and down travel is made smooth through the use of constant force balance system that is concealed within the jamb. Lower sash operates and tilts in for easy cleaning. A unique locking balance shoe makes sash removal easy.
- C. Finish: Standard color options include white and clay (interior and exterior). Black laminated exteriors available with white or painted black interior. Bronze painted exteriors available with white interior.
- D. Glazing: All units include 7/8" double pane LoE 366 insulated glass as standard. 1" laminated glass available (standard on impact rated products). 1 1/4" triple glazing available with several LoE options. Glass is set with snap-in glazing beads on the exterior and a 2-part structural sealant on the interior. A wide array of other glass combinations is offered including clear, tinted, tempered, and obscure.
- E. Hardware: All units contain color-matched cam action locks and keepers. Two locks are standard on rough opening widths greater than or equal to 28". Spring-loaded, retractable tilt latches are located on the top rail of lower sash. All hardware is color matched to the unit and is attached with color-matched screws. Factory or field-applied Window Opening Control Device (WOCD) is available as an option.
- F. Screens : Screen construction is charcoal color fiberglass mesh set into an aluminum frame. BetterVue™ Screen option is available. All screen frames are color matched to the unit. Screens reside in extruded channels and are held in place retractable pins. Screens are easily removed from the inside by retracting the pins and tilting inward. Our insect screens are intended to allow air and light in and keep insects out. The screen is not intended to stop children, adults or animals from falling out an open window.
- G. Grilles: Rectangular aluminum inner grilles, available as 3/4" profiled, are color matched to the unit and are installed within the air space. Windsorlite (WDL) simulates true divided lite, but is created by adhesively fixing the interior and exterior bars to the surfaces of the insulated glass. Two WDL bar shapes are available: 5/8" and 7/8" wide putty.

# New Next Dimension Series

## SINGLE HUNG

## SPECIFICATIONS

- H. Mulls: Mulls groups within a certain size range will utilize T-Bar mullion posts in one continuous frame. When T-Bars mullions are not possible, individual units are mullied using vinyl frame connectors and drip cap over all vertical mulls. Depending on the size, configuration, and structural requirements, mullied units may include galvanized steel structural or aluminum reinforcement bars.

## **PART 3 - EXECUTION**

### **3.01 EXAMINATION**

- A. Verify that there is no visible damage to the unit before installation.

### **3.02 INSTALLATION**

- A. Verify the rough opening is of the recommended size and that it is plumb, level, and square.
- B. Install the window unit in accordance with the manufacturer's recommendations.
- C. Install sealants, backing material, and insulation around opening perimeter in accordance with Section 07900 and Section 07920.

### **3.03 ADJUSTMENT AND CLEANING**

- A. Operate unit and verify that all hardware operates freely. Make any adjustments necessary.
- B. Cover the window unit to avoid damage due to spray paint, plaster, and other construction operations.
- C. Remove all visible labels and instructions.
- D. Final cleaning of glass in accordance of Section 01710.