

# Pinnacle Series

## PRIMED RADIUS

### MEASUREMENT CONVERSIONS

STANDARD BRICKMOULD												
Size Referenced	Daylite Opening		Glass Size		Frame Size		Rough Opening		Unit Size		Masonry Opening	
Daylite Opening	Dimension Needed											
			Width	+1	Width	+3	Width	+3 3/4	Width	+5 13/16	Width	+6 5/16
Glass Size	Width	-1			Width	+2	Width	+2 3/4	Width	+4 13/16	Width	+5 5/16
	Height	-1			Height	+2	Height	+2 1/2	Height	+4 7/32	Height	+4 23/32
Frame Size	Width	-3	Width	-2			Width	+3/4	Width	+2 13/16	Width	+3 5/16
	Height	-3	Height	-2			Height	+1/2	Height	+2 7/32	Height	+2 23/32
Rough Opening	Width	-3 3/4	Width	-2 3/4	Width	-3/4			Width	+2 1/16	Width	+2 9/16
	Height	-3 1/2	Height	-2 1/2	Height	-1/2			Height	+1 23/32	Height	+2 7/32
Unit Size	Width	-5 13/16	Width	-4 13/16	Width	-2 13/16	Width	-2 1/16			Width	+1/2
	Height	-5 7/32	Height	-4 7/32	Height	-2 7/32	Height	-1 23/32			Height	+1/2
Masonry Opening	Width	-6 5/16	Width	-5 5/16	Width	-3 5/16	Width	-2 9/16	Width	-1/2		
	Height	-5 23/32	Height	-4 23/32	Height	-2 23/32	Height	-2 7/32	Height	-1/2		

3 1/2 FLAT CASING												
Size Referenced	Daylite Opening		Glass Size		Frame Size		Rough Opening		Unit Size		Masonry Opening	
Daylite Opening	Dimension Needed											
			Width	+1	Width	+3	Width	+3 3/4	Width	+8 7/8	Width	+9 1/8
Glass Size	Width	-1			Width	+2	Width	+2 3/4	Width	+7 7/8	Width	+8 1/8
	Height	-1			Height	+2	Height	+2 1/2	Height	+5 3/4	Height	+6
Frame Size	Width	-3	Width	-2			Width	+3/4	Width	+5 7/8	Width	+6 1/8
	Height	-3	Height	-2			Height	+1/2	Height	+3 3/4	Height	+4
Rough Opening	Width	-3 3/4	Width	-2 3/4	Width	-3/4			Width	+6 5/8	Width	+5 1/8
	Height	-3 1/2	Height	-2 1/2	Height	-1/2			Height	+4 1/4	Height	+3 1/4
Unit Size	Width	-8 7/8	Width	-7 7/8	Width	-5 7/8	Width	-6 5/8			Width	+1/2
	Height	-6 3/4	Height	-5 3/4	Height	-3 3/4	Height	-4 1/4			Height	+1/2
Masonry Opening	Width	-9 1/8	Width	-8 1/8	Width	-6 1/8	Width	-5 1/8	Width	-1/2		
	Height	-7	Height	-6	Height	-4	Height	-3 1/4	Height	-1/2		