

# Revive Series

## VINYL DOUBLE HUNG

### DESIGN PRESSURE VALUES / MINIMUM AND MAXIMUM MEASUREMENTS

Operating Double Hung					
Series	Window Type	Performance Level	Size	Performance Grade	Air Infiltration (cfm/ft <sup>2</sup> )
Revive Vinyl	Double-Hung	Standard	3684-3	LC-PG30-H	0.24
Revive Vinyl	Double-Hung	Standard	4884-2	LC-PG30-H	0.19
Revive Vinyl	Double-Hung	Standard	3666-2	LC-PG40-H	0.15
Revive Vinyl	Double-Hung	Standard	4884-1	LC-PG30-H	0.16
Revive Vinyl	Double-Hung	Standard	3666-1	R-PG40-H	0.21
Revive Vinyl	Double-Hung	Standard	4566-1	R-PG30-H	0.2
Revive Vinyl	Double-Hung	DP Upgrade	3666-2	LC-PG45-H	0.15
Revive Vinyl	Double-Hung	DP Upgrade	3672-1	R-PG50-H	0.22

**Notes:**

Ratings listed were determined using AAMA/WDMA/CSA 101/I.S.2/A440 procedures

Ratings listed qualify all sizes at or below the test size

Glass type and thickness complies with ASTM E 1300 for the DP Values to a minimum of DP-40.

Minimum and Maximum Measurements			
Minimum RO Width	Minimum RO Height	Maximum RO Width	Maximum RO Height
<b>Operating</b>			
1-6	2-6	4-0	7-0