

Pinnacle Select Series


CLAD AWNING

ELEVATIONS : OPERATING / STATIONARY


SCALE: 1/8" = 1'-0"

Masonry Opening Rough Opening Frame Glass	2-0 3/4	2-4 3/4	2-6 3/4	2-8 3/4	3-0 3/4	3-6 3/4	4-0 3/4	4-6 3/4	5-0 3/4
	2-0 3/4	2-4 3/4	2-6 3/4	2-8 3/4	3-0 3/4	3-6 3/4	4-0 3/4	4-6 3/4	5-0 3/4
	2-0	2-4	2-6	2-8	3-0	3-6	4-0	4-6	5-0
	18 3/4	22 3/4	24 3/4	26 3/4	30 3/4	36 3/4	42 3/4	48 3/4	54 3/4
1-6 1/2 1-6 1/2 1-6 12 3/4	2418	2818	3018	3218	3618	4218	4818	5418	6018
1-8 1/2 1-8 1/2 1-8 14 3/4	2420	2820	3020	3220	3620	4220	4820	5420	6020
2-0 1/2 2-0 1/2 2-0 18 3/4	2424	2824	3024	3224	3624	4224	4824	5424	6024
2-4 1/2 2-4 1/2 2-4 22 3/4	2428	2828	3028	3228	3628	4228	4828	5428	6028
2-6 1/2 2-6 1/2 2-6 24 3/4	2430	2830	3030	3230	3630	4230	4830	5430	6030
3-0 1/2 3-0 1/2 3-0 30 3/4	2436	2836	3036	3236	3636	4236	4836	5436	6036
3-6 1/2 3-6 1/2 3-6 36 3/4	2442	2842	3042	3242	3642	4242	4842	5442	6042
4-0 1/2 4-0 1/2 4-0 42 3/4	2448	2848	3048	3248	3648	4248	4848	5448	6048
4-6 1/2 4-6 1/2 4-6 48 3/4	2454	2854	3054	3254	3654	4254	4854	5454	6054
5-0 1/2 5-0 1/2 5-0 54 3/4	2460	2860	3060	3260	3660	4260	4860	5460	6060

OPERATION




OPERATING




STATIONARY

OTHER GRILLE PATTERN



PRAIRIE



DIAMOND

UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD**
- ADD 2 13/16" TO FRAME WIDTH
 - ADD 1 3/4" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG**
- ADD 6 1/2" TO FRAME WIDTH
 - ADD 3 5/8" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTE:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING